

NOTES:

1. THICKNESS OF GRANULAR BASE LAYER DEPENDENT UPON SPECIFIC SITE & LOADING CONDITIONS.
2. ¼" CHIP CLEAR OR OTHER SUITABLE CLEAR STONE CAN BE USED FOR GRANULAR BASE LAYER TO INCREASE WATER STORAGE CAPACITY.
3. IF CLEAR STONE IS USED FOR GRANULAR LAYER, THEN A NONWOVEN GEOTEXTILE SHOULD BE USED AS A SEPARATION LAYER BETWEEN THE CLEAR STONE BASE AND THE SUBGRADE.
4. DRAINAGE SYSTEM OF THE PERMEABLE PAVEMENT SYSTEM SHOULD BE DESIGNED TO ACCOMMODATE EXPECTED INFILTRATION RATES, STORAGE CAPACITIES, OUTLET FLOW RATES, AND OTHER SITE SPECIFIC CONDITIONS.
5. SUBGRADE SHOULD BE SLOPED TO AID IN DRAINAGE.
6. ALL DIMENSIONS IN mm UNLESS STATED OTHERWISE.
7. THIS DRAWING IS FOR CONCEPTUAL DESIGN PURPOSES ONLY, NOT FOR CONSTRUCTION.

